

**Features**

- Noise Figure  $\leq 1.0$  dB
- Unconditionally Stable at all temperatures
- Internally Regulated DC Voltage
- 50 Ohm Matched Input/Output
- Field Replaceable 3.5mm SMA connectors
- Excellent Group Delay and Phase Linearity
- 0.009 inches diameter RF In/Out feed through
- Operating Temp. -55 C to +85 C
- Gain change with temperature: 0.022dB/ °C
- NF change with temperature: 0.1dB/ 10 deg °C
- 3 Year Warranty

**Specifications (23 °C)**

Parameter	Min	Typ	Max	Units
Frequency Range	2.8	-	3.3	GHz
Noise Figure*	-	-	1.0	dB
Gain	26	-	-	dB
Gain Flatness (+/-)	-	$\pm 0.7$	$\pm 1$	dB
P1 Output Power	+10	-	-	dBm
Input VSWR	-	-	1.8:1	
Output VSWR	-	-	1.8:1	
Operating Temperature	-55	-	+85	°C
Non-Operating Temp Range	-65	-	+125	°C
RF Input Power (no-damage)	-	-	+13	dBm
Humidity (non-condensing)	-	-	95	%
Voltage	+15	+15	+15	VDC
Current	-	105		mA
Input Impedance	50			Ohms
RF Connector	3.5mm SMA - Female			
Dimensions	29.9 x 18.7 x 7.6			mm


**Options**


- Optimized Performance over Selected Bandwidth
- Internally DC Block Input (Output DC Block Standard)
- Hermetically Sealed Package
- Improved Gain Flatness
- Improved IN and OUT VSWR
- Gain and Phase matching
- Lower Noise Figure



\* Noise Source used for measurement from 0.01 to 26.5 GHz is HP346C .  
NF Uncertainty (approx. 0. 1dB). 0.05 dB due to ENR of HP 346C; and 0.05 dB, due to the gain modulation of the unit, caused by the HP 346C source impedance change in the ON and OFF state.

**Typical Data**






Approx. Actual Size



**Mounting Drawing**



**Drop In**

